

HD-SDI / HDMI DIGITAL VIDEO CONVERTERS

# CONNECT

## DUAL-BATTERY CONVERTERS

The world's  
smallest 3G  
Converters

Convert  
uninterrupted  
anywhere



**H2S**  
HDMI → HD-SDI

Continuous Power\*



**S2H**  
HD-SDI → HDMI



Test Pattern  
& Audio Tone  
Generator



Built-in  
Pull-down  
removal

Tiny, reliable, cascadable & future proof



Modular  
Design

Stack up to  
three units  
for super-fast  
simultaneous  
charging



**Connect Converters are the ultimate battery powered, in-the-field converter tool for any situation. With 3G/HD/SD-SDI and HDMI connectivity, internal and external battery options and Atomos' patent pending Continuous Power technology, you can convert anytime, anywhere.**

Built for convenience, Connect Converters are lightweight and fit in your pocket. Powered by battery or AC, they provide 3:2 pulldown removal, test pattern and audio signal generation and even have a built-in flashlight for use in dark locations.

At Atomos we're all about innovation, so we've made Connect incredibly flexible. They're stackable and modular and you can cascade and power them from one source.

# CONNECT

## DUAL-BATTERY CONVERTERS



### Connect 3G/HD/SD-SDI & HDMI

Convert any HD/SD-SDI or HDMI signal, including 3G. Choose S2H for HD-SDI→HDMI and H2S for HDMI→HD-SDI

### S2H HD-SDI→HDMI

All SDI types to HDMI; pulldown removal included

### H2S HDMI→HD-SDI

HDMI to all SDI types pulldown removal included

### Battery or AC power: 2 hours, 2 days or continuous supply

A portable device without a power supply is useless, but that will never happen with Connect converters.

With flexible battery and power options, you're covered for any eventuality – even an unexpected power loss. A built-in battery ensures that the show goes on if all else fails.

Multiple, stackable external batteries can be swapped without powering down, and any Connect battery configuration acts as a backup to AC power, at the same time as being charged from it.



### Connect:

Attach to, and power, Atomos Ninja, Ninja-2 and Samurai.



### In the field

- Very small and lightweight
- Battery powered (no AC needed)
- Full day's use from one battery
- Use with a mixture of devices

### In the studio

- Integrate affordable HDMI equipment throughout your SDI infrastructure
- Connect HDMI devices to SDI switchers, routers and signal feeds

### Editing & capture

- Affordable monitoring with SDI to HDMI conversion
- Easy conversion for cameras, decks, and capture cards

### The Ultimate Video Tool

Not just the world's smallest 3G converter! A must have tool for professional everyday use



TEST PATTERN GENERATOR

Convenient broadcast-quality test patterns for equipment verification on the fly anytime, anywhere! Also includes Audio Tone Generator

### 3:2 3:2 PULLDOWN REMOVAL

Realtime Pulldown Removal. Extract 24P/30P from 60i & 25P from 50i or PSF equivalents

### FLASHLIGHT

A built-in LED torch, so you can see what you're connecting to in the dark!

### TC TIMECODE PASS-THROUGH

HDMI→HD-SDI / HD-SDI→HDMI

### What's in the box



<b>Dimensions</b>	45.0mm (w) x 76.5mm (l) x 30.0mm (h)	<b>USB Interface</b>	Firmware Update Interface ONLY
<b>Weight</b>	115 grams/4.0 Oz. (without ext. battery)   215 grams/7.6 Oz. (with ext. battery)	<b>Video Input</b>	S2H: 3G/HD/SD-SDI x 1   H2S: HDMI x 1
<b>Power Consumption</b>	2W while converting	<b>Video Out</b>	S2H: 3G/HD/SD-SDI x 1 and HDMI x 1   H2S: 3G/HD/SD-SDI x 2
<b>Batteries (NP Series, 7.4V - 16.8V)</b>	<ul style="list-style-type: none"> <li>• Internal up to 1 hour • 2600mAh - 10hrs (included)</li> <li>• 5200mAh - 20hrs (optional) • 7800mAh - 30hrs (optional)</li> <li>• AC Power Supply 100-240V (included) • D-Tap Adaptor (optional)</li> </ul>	<b>Audio (In/Out)</b>	Embedded Audio 2ch, 24bit
<b>Continuous Power (Patent Pending)</b>	Connect acts as a battery, feeding continuous power into your Ninja, Samurai, or another Connect.	<b>Timecode</b>	SDI: Sony, Canon, Panasonic, Arri, RED HDMI: Sony, Canon Timecode, Canon Start/Stop
<b>Built-in 3:2 and 2:2 Pulldown Removal</b>	• 25PsF (50i)→25P • 30PsF (60i)→30P • 24p (3:2-60i)→24P	<b>Supported Formats (In/Out)</b>	1080p60, 1080p59.94, 1080p50, 1080i60, 1080i59.94, 1080i50, 1080p30, 1080p29.97, 1080p25, 1080p24, 1080p23.98, 1080psf30, 1080psf29.97, 1080psf25, 1080psf24, 1080psf23.98, 720p60, 720p59.94, 720p50, 486i59.94, 486i59.94, 576i50
<b>Test Pattern Generator</b>	SMPTE 75%, Colour Bars 75 & 100%, SDI EQ/PLL Pathological, Audio Tone 1kHz @ -20dBfs		



**ATOMOS (HQ)**  
5 Eastbourne St.  
Windsor VIC 3181  
Australia

Enquiries: [sales@atomos.com](mailto:sales@atomos.com) | Support: [support@atomos.com](mailto:support@atomos.com) | Telephone: +61 3-9999-5908 | [www.atomos.com](http://www.atomos.com)