1405 Pioneer St., Brea, CA 92821 888.975.1368 | info@kanexpro.com

4K HDMI 1x2 Splitter with HDCP2.2

1x2 HDMI DA w/ HDCP2.2, 4K Cinema resolutions & Smart EDID Control

MPN: SP-HD20-1X24K



The KanexPro SP-HD20-1X24K is

an one input, two output HDMI Distribution Amplifier engineered to split 4K quality videos or high res images from one source to two 4K displays with resolutions up to 4K@60Hz and HDCP2.2 specifications. Built-in EDID management allows optimal resolution to be selected and properly outputted to avoid response time and delays.

The conforming outputs also have the ability of buffering and amplifying all the HDMI signals. It can achieve long distance transmission of HDMI signals up to 50 feet (15 meters) or can be combined with our HDBaseT™ Extenders to route distances up to 330 feet (100 meters).

FEATURES

- Distribute one 4K HDMI video and audio signals to two displays
- True 4K@60Hz UHD, 1080p & 3D resolutions
- 4Kx2K @30Hz with 24bit RGB, YCBCR 4:4:4 & YCBCR 4:2:2
- 4Kx2K @60Hz with 12bit YCBCR 4:2:0
- Conforms to High Speed HDMI specifications:
- (Deep color, HD lossless audio formats & Lip Sync)
- EDID Selector for optimal resolutions
- HDCP 2.2 compliant
- Built-in Smart EDID Control
- Front-panel LED's for input/ output signal presence
- Includes 5V DC external power supply

SPECIFICATIONS

Signal Input/Outputs:

- Input DDC Signal: 5 Volts p-p (TTL)
- •Input & Output Signal: High Speed HDMI Spec 2.0a

Input Ports: 1 x HDMI (Female)
Output Port: 2 x HDMI (Female)

Operating Frequency: Vertical Frequency

Range: 50/60Hz Supported Resolutions:

- 480i ~1080p50/60, 4Kx2K@24/30
- 4Kx2K@60Hz with 12bit YCBCR 4:2:0
- VGA~UXGA

Power Requirements:

- Power Consumption: 2W
- External Po

Regulatory Approvals:

- Converter Unit: FCC, Ce, UL
- Power Supply: UL, Ce, FCC

Environment Operating Temperature:

- \bullet Operating Temperature: 0°C ~ 40°C / 32°F ~ 104°F
- \bullet Storage Temperature: -20°C ~ 60°C / -4°F ~ 140°F

Dimensions: 2.52" (W) x 6.10" (D) x .67" (H)

Weight: 6.35 oz. (180g) Package Contents:

- HDMI 1X4 Splitter
- 5V, 2A Power Supply
- Operation Manual



ABOUT KANEXPRO