

Walk-and-Talk™ Lightning™

Interactive Whiteboard

Collaborate
Inspire
Captivate



* Walk-and-Talk board shown on Power and Data Track System over an Access™ Commercial Series Markerboard



Interruption-free meetings and classes



Intuitive remote control



PolyKey™ Technology for instant plug-and-play

Calibration-free

Introducing PolyVision's Walk-and-Talk™ Lightning™, the world's first calibration-free interactive whiteboard.

Walk-and-Talk Lightning eliminates the need to perform the four, eight, or sixteen point calibration of standard interactive whiteboards so you can enjoy interruption-free meetings and classes!

If your projected image is ever out of alignment, simply press the projection button on the Walk-and-Talk remote control. Lightning's Photonic Array Technology™ allows you to begin using the board instantly.

The Freedom to Move and Inspire

Walk-and-Talk Lightning boards include all the benefits of the regular Walk-and-Talk, making it the easiest to use board on the market. Walk-and-Talk boards allow you to walk among your audience

while controlling your presentation and whiteboard activities through an incredibly intuitive remote control. The remote puts the power and flexibility of the Walk-and-Talk board in your hands, allowing you to project, write with projected ink, erase, save, print, and access the Web.


Launch Your Ideas, Not Your Board's Software

Use your Walk-and-Talk Lightning board with any PC or laptop, any time, any place, with PolyKey™ Technology. PolyKey eliminates the need to pre-load or learn proprietary board software so you can literally plug-and-play.

Walk-and-Talk Lightning Interactive Whiteboard: Calibration-free presentations.

POLYVISION
A Steelcase Company

Features and Technical Specifications



	WTL 1400	WTL 1600	WTL 1800
Dimension A (HXW)	44.6 in. x 47.8 in. (1133mm x 1214mm)	52.6 in. x 67.8 in. (1336mm x 1722mm)	52.6 in. x 97.8 in. (1336mm x 2484mm)
Dimension B (HXW)	35.0 in. x 45.0 in. (889mm x 1143mm)	43.0 in. x 65.0 in. (1092mm x 1651mm)	43.0 in. x 95.0 in. (1092mm x 2413mm)
Dimension C (Diagonal)	57.0 in. (1448mm)	78.0 in. (1981mm)	104.0 in. (2642mm)
Dimension D (Depth)	4.3 in. (110mm)	4.3 in. (110mm)	4.3 in. (110mm)
Resolution	8000 x 8000	8000 x 8000	8000 x 8000
Weight	52 lbs (23.6kg)	78 lbs (35.4kg)	104 lbs (47.0kg)

Surface Material

Touch-sensitive, Teflon® coated, dry erase, low glare, projection-optimized surface

Power Requirements

USB powered, except with optional wireless kit

Certification

FCC class A, CE

Product Feature

- Calibration-free projection

Driver/Software Features

- Instant loading PolyKey™ driver for walk-up-and-use operation or Webster™ software for advanced users
- On screen keyboard and image mark-up
- Print or save images in PDF, BMP, TIFF, PNG, or JPG image format (other options available with Webster software)

Accessories (Included)

- Remote control with built-in touch pad and trigger-click technology (two AA batteries included)
- Active infrared eraser with two spare eraser pads (two AAA batteries included)
- 15 foot (4.6m) USB cable
- USB PolyKey™ with driver
- Stylus
- Installation and Operation Manual
- Reversible remote control holder, mounts to either side of board
- Wall mounting brackets
- Two remote control lanyards

Recommended Computer Requirements

Microsoft Windows®:

32 megabytes RAM, Pentium 250 MHZ processor or better Windows 98, 2000, ME, XP, or tablet XP

One USB port

Warranty

- Two-year limited warranty, free upgrade to five years upon product registration

Options

- Sliding Power and Data Track System
- Integrated room-blasting infrared wireless computer connection
- "Feather-touch" Adjustable Height Stand
- Free Webster software for Windows
- RM Easiteach® Studio educational software

Authorized PolyVision Dealer

PolyVision Corporation
1.800.620.POLY
info@polyvision.com
www.polyvision.com

POLYVISION
A Steelcase Company