

## VEO-SPH44

# DISTRIBUTION AMPLIFIER / SPLITTER 1x4 HDMI 2.0 DISTRIBUTION AMPLIFIER / SPLITTER



#### **PRODUCT OVERVIEW**

Ecler VEO-SPH44 is a professional 1x4 HDMI 2.0 distribution amplifier/splitter. It supports HDR formats and HDMI data rate up to 18Gbps at 4K/UHD@60Hz video resolution with 4:4:4 chroma sampling. It includes EDID management in three different modes and it is HDCP 2.2 compliant. VEO-SPH44 guarantees seamless integration for all applications that require latest 4K/UHD and HDR sources and displays.

#### **KEY FEATURES**

- Simultaneously displays UItra Hi-Definition source on up to four UItra HD displays
- Supports resolution up to Ultra HD 4Kx2K (4096x2160@60Hz YUV 4:4:4)
- Three EDID setting modes
- HDCP 2.2/1.4 Compliant
- Supports 36 bit Deep Color
- Supports LPCM 7.1, Dolby TrueHD, Dolby digital Plus, and DTS-HD Master Audio
- Supports HDR and 3D contents
- Supports up to 18Gbps video data rate

### **APPLICATIONS**

- Retail shops
- Fitness Center
- Sports Bar
- Restaurants
- Hotels
- Residential applications

TECHNICAL DATA

## Audio and Video performances

Supported Resolutions Up to 4096x2160@60Hz

4096x2160@24/25/30/50/60Hz, 3840x2160@24/25/30/50/60Hz,2048x1080p

1080p@23.98/24/25/29.97/30/50/59.94/60Hz, 1080i@50/59.94/60Hz, 720p@50/59.94/60Hz, 720p@50/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/60/59.94/6

576p, 576i, 480p, 480i

Colorspace RGB, YCbCr

**Chroma Subsampling** 4:4:4, 4:2:2, 4:2:0

1/3



Color depth 8-bit, 10-bit, 12-bit

HDR HDR 10

Signal Bandwidth Gbps

HDCP 2.2/1.4 Compliant

Audio Formats PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby Digital, DTS 5.1, Dolby TrueHD, DTS-HD Master Audio

Sample Rate 32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz

Bit rate up to 24-bit

**HDMI Distance** up to 10 meters (33 feet) with Ecler VEO cables

Operation Temperature -5 to +40°C (+41 to +104°F)

**Humidity** 5 - 90% RH (no condensation)

Power Consumption 2 W Maximum

Power Supply AC100~240V 50/60Hz Output: DC 5V/1A

## MISCELLANEOUS

**Dimensions W x H x D** 150mm x 17mm x 65mm / 5.9" x 0.67"x 2.56"

Weight 245g / 0.54 lb

### **MECHANICAL DIAGRAMS**







