# Blackline **FI2**

Compact two-way passive system

#### features

- Compact two-way passive system
- Multi-angle birch ply enclosure
- User rotatable 80° x 50° horn
- Top hat fitting for tripod mounting
- Five year limited warranty

#### applications

- Live club performance
- Floor monitor
- Club installs



The Blackline F12 is a high power, compact 2-way system with a 12" (300mm) LF driver and a 1" (25mm) exit compression driver mounted on a rotatable 80° x 50° constant directivity HF horn. It is the ideal choice for full-range applications calling for an efficient, reliable workhorse that is equally suitable for fixed installations and quick deployment mobile operations.

### technical specifications


	-
TYPE	Compact, two-way passive, multi-angled, vented
FREQUENCY	
RESPONSE (I)	$65Hz-18kHz \pm 3dB$
DRIVERS	12" (300mm) bass driver
	I" (25mm) exit compression driver
RATED POWER (2)	300W AES, 1200W peak
RECOMMENDED	400-650W into 4 ohms
AMPLIFIER	
SENSITIVITY (3)	97dB
MAXIMUM SPL (4)	120dB continuous, 126dB peak
IMPEDANCE	8 ohms nominal
DISPERSION (-6dB)	80° horizontal, 50° vertical
CROSSOVER	2kHz passive
ENCLOSURE	38 litre, multi-laminate birch ply
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4
FITTINGS	10 x M8 inserts
	Top hat fitting
	4 x M8 bracket inserts
DIMENSIONS	(W) 398mm x (H) 571mm x (D) 365mm
	(W) 15.6ins x (H) 22.5ins x (D) 14.3ins
WEIGHT	21kg (46lbs)
	<b>U</b> ( )

Century Point, Halifax Road, Cressex Business Park, High Wycombe, Buckinghamshire HP12 35L, England. Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669 E-mail: info@martin-audio.com All information is Copyright © 2003 Martin Audio Ltd.



## www.martin-audio.com







<u>F12</u>