

# The StarBoard BT-1 from Hitachi providing the flexibility to teach or present from anywhere in the room.



The StarBoard BT-1 is a lightweight graphics tablet that when connected to a projector and PC, enables presentations to be displayed on a large screen and the computer to be controlled remotely from anywhere in the room. A cordless pen is used to annotate onto the tablet, which communicates wirelessly with an adaptor connected to the computer's USB port.

## Portable inspiration

The StarBoard BT-1 pad is ideal for use during a lesson, training session or meeting. Simple to operate and robust it can easily be carried around lecture halls, schoolrooms, boardrooms and any other presentation environment.

By moving the pen across the surface of the tablet, the user can control the mouse movements of the PC. The pen facilitates both left and right mouse clicks, removing the need to use the PC directly. Several tablets can be used in a session if desired, so that different people can interact with the computer when control is transferred to them.



**HITACHI**  
Inspire the Next

# The StarBoard BT-1 from Hitachi providing the flexibility to teach or present from anywhere in the room.

## Technical Specifications

<b>Tablet dimensions</b>	8" x 7" x 2" (250mm x 243mm x 30mm)
<b>Working area</b>	6" x 4.5" (152mm x 114mm)
<b>Working environment</b>	Windows XP
<b>Resolution</b>	500 lines per inch
<b>Maximum position</b>	X: 3000 Y: 2250
<b>Macro key</b>	None
<b>Accuracy (center area)</b>	+/- 1mm (pen vertical to surface)
<b>Accuracy (boundary 1/2" area)</b>	+/- 2mm (pen vertical to surface)
<b>Jitter (center area)</b>	+/- 1 point (pen vertical to surface)
<b>Jitter (boundary 1/2" area)</b>	+/- 3 points (pen vertical to surface)
<b>Weight</b>	470 grams (1.04 lbs)
<b>Data interface</b>	USB, Bluetooth
<b>Battery</b>	(2) AA rechargeable batteries
	BT-1 – Pen
<b>Pen</b>	Pen with mouse select button
<b>Pen Battery</b>	(1) AAA battery
<b>Proximity</b>	8mm minimum
	BT-1 – Bluetooth Module
<b>Bluetooth module</b>	Fully compliant with Bluetooth v1.1
<b>Module type</b>	Bluetooth v1.1 Class B
<b>Module chip</b>	Microtune
<b>Module interface</b>	Serial port interface (SPI)
<b>Module clock</b>	1.5 MHz
<b>Operating voltage</b>	3V DC +/- 5%
<b>Operating temperature</b>	32° F - 112° F (0°C - 45° C)
<b>Storage temperature</b>	-4° F - 112° F (-20°C - 45° C)
<b>Operating humidity</b>	0-70% (non-condensing)
	BT-1 – Product Performance
<b>Compatible dongle</b>	SiliconWave, CSR
<b>Multiple connections</b>	4 tablets
<b>Link distance</b>	up to 10 meters (32.8 feet)
<b>Tablet report rate</b>	120 reports per second (in USB mode)

### Further information:

#### Hitachi Software Engineering (UK) Limited

10 Old Bailey  
London EC4M 7NG United Kingdom  
Tel: +44 (0)20 7038 1030  
Fax: +44 (0)20 7038 1130  
Email : sales@hitachi-software.co.uk

#### Hitachi Software Engineering France S.A.S

7th Floor, 64 rue du Dessous des Berges  
75013 Paris, France  
Tel: +33 (0) 153 827 600  
Fax: +33 (0) 153 827 619  
Email : starboard@hitachisoft-eu.com

#### Hitachi Software Engineering Europe A.G.

Neues Kranzler Eck, Kurfürstendamm 22  
D-10719 Berlin, Germany  
Tel : +49 (0)30 8877 2600  
Fax : +49 (0)30 8877 2610  
Email : starboard@hitachisoft.de

**HITACHI**  
Inspire the Next

www.hitachisoft-eu.com