

# Versatile Business Presentation Tool **Visual Presenter MO-1**

can be used in various business situations.

Show documents, small items and operation of the small equipment clearly on the monitor or screen. Provide persuasive power and increase the depth of understanding of your presentation. Light weight with compact design, you can carry the MO-1 wherever you need to go. Take it with you for important meetings with your clients or even on business trips.


Use the MO-1 during meetings for unlimited purposes, such as to review written contracts, to magnify small product parts, to demonstrate smart phones or tablets, or even as a web cam for online meetings. Furthermore, you can use the MO-1 as a scanner to transform documents, architectural models and product parts into digital data instantly.

# What is a Visual Presenter?

A visual presenter is an image capture device used to project the images of documents and three sional objects placed underneath the camera to a screen through a projector or to a digital TV monitor. The equipped zoom lens allows you to adjust the size of the image as you wish. A visual presenter can also be called a document camera or visualizer.



### •Wireless model: MO-1w / Receiver: VPR-1



**VPR-1 Specifications** Operating temperature 0°C~40°C

Communication distance Approx. 10m (32.8feet) (Varies depending on the operating

Output : 5V, 2A

192 kHz x 24 hit Power consumption 5.5W (5V / 1.1A) (Excluding the AC adapter

ation Max. 8 units

Input : 100V-240V, 0.5A, 50/60Hz

HDMI OUT (Type A) VGA (640x480)60Hz/75Hz, SVGA (800x600)60Hz/75Hz

LET'S Start |CT in Education with Document Camera ! Visit the ELMO global website to understand what a document camera is in 13 different languages. The ELMO global website

document camera and how the ELMO document camera is used

and supported by teachers worldwide. http://www.elmoglobal.com

introduces you to the useful and effective ways of using the

1152x864 (60Hz), 1280x960(60Hz) 480p. 576p. 720p. 1080i. 1080p

XGA (1024x768) 60Hz/75Hz, WXGA (1280x768) 60Hz.

L83 x W80 x H31 (mm) L 3 1/4" x W 3 1/8" x H 1 1/4"

WXGA (1280x800) 60Hz, SXGA (1280x1024) 60Hz/75Hz

## MO-1/MO-1w Specifications

Model	MO-1	MO-1w
Power source	DC5V(AC adapter) / Power supply from USB (USB operation only)	
Power consumption	4.2W(Standby 0.25W)/ USB 3.3W	7.4W(Standby 0.15W)/ USB 3.5W
lmage pick-up element	1/3.2" 5M pixel CMOS Sensor	
Effective pixels	Horizontal 2048, Vertical 1536	
Lens	F2.9	
Shooting area	Max.257mmx342mm (10 7/64" x 13 15/32")(WXGA/ XGA/ VGA	
Focus	AF(One-push)/ MANUAL	
White balance	AUTO/ MANUAL	
Digital zoom	8 x	
Flicker correction	Provided	
HDMI output	1080i (30fps), 720p (30fps)	N/A
	720p (60fps)*	
Analog RGB output	WXGA/ XGA (20fps)	N/A
	When power is OFF: External RGB input	
	(Only when AC adapter is used)	
USB output	Type B(Mini), WXGA/ XGA (20fps), VGA (20fps),	
	1080p (15fps), 720p (30fps)	
WHDI output (Uncompressed wireless image transmission)	N/A	WXGA/ XGA, 1080i(30fps)
		720p(30fps)/ 720p(60fps)*
Input selection	HDMI/ RGB/ USB/ External	WDHI/ USB/ External
Input terminal	Analog RGB(D-Sub), HDMI(Type A(standard)HDMI compliant)	
Image rotation	Provided Camera Still image : 0°/90°/180°/270°	
	Camera live image : 0°/180°	
Microphone	Built-in (USB/ HDMI)	Built-in (USB/ WHDI)
Still image capture	Provided	
SD card slot	Provided	
Illumination	White LED	
Weight	550g (1.2lbs)	590g (1.3lbs)
Accessories	AC adapter/ Power cord/ CD-ROM (Application software	
	"Image Mate"/ Instruction manual/ Quick start guide)/	
	USB cable/ Safety instructions	

When 720p 60fps is selected, the angle of view becomes narrower than 720p 30fps.

# ELMO's Helping to Provide a Greener Future for Our Children

is ELMO product complies with RoHS Directive 2002/95/EC (Restriction Of the use of ertain Hazardous Substances in electronic equipment). This compliance helps to ensure a

ELMO CO., LTD.

nealthier and greener environment for all our children

6-14, Meizen-cho, Mizuho-ku Nagoya, 467-8567, Japan

#### **ELMO Europe SAS** German Branch Headquarters Immeuble Elysées La Défense Hansaallee 201, Haus 1 7C Place du Dôme 92056 Paris La Défense France Germany

Tel. 33 (0)1 73 02 67 06 Tel. 49 (0)211 5447 5640

40549 Düsseldorf

## **ELMO USA Corp.** Headquarters Plainview, NY 11803, U.S.A. Tel. (516) 501-1400 Fax. (516) 501-0429

E-mail: elmo@elmousa.com


West Coast Branch 5676 Corporate Avenue Tel. (714) 828-8457 Fax. (714) 828-8429 Web : http://www.elmousa.com

# ELMO (Beijing) Co., Ltd.

Cypress, CA 90630, U.S.A. Plaza, No.93, Jianguo Road. Chaoyang District, Beijing 100022 ,P.R.CHINA Tel: 86 10 5960 3890



# ELMO









Printed in Japan (KW) 03/2012

ISO 9001

ISO 14001



**©High-precision visual presentation tool** 





Digital zoom

Reproduce objects in true color while showing details clearly. High definition and smooth video image can be fully displayed on an HD TV screen.

**○Simple data import to a computer** 


Camera head Flexible camera arm and head allow you to enlarge various subjects from different

Intuitive and friendly operation. Easy to set up and use. When connecting to a computer, the MO-1 can be used as a three dimensional scanner. (Close-up to 7cm (2 3/4") distance from the objects.)

**Network communication tool** 



Built-in Microphone allows you to use the MO-1 as a web cam for important online meetings.



**OMO-1's other useful features** 

# Interface



SD card slot

Still images can be stored on the SD card.

CRA-1



HDMI input/output

is possible.



Powered via USB\*

High definition image presentation No AC adapter is required when the MO-1 is connected to a computer by the USB cable.

\*when in USB mode

