



BOSCH
Invented for life

DCN-WAP Wireless Access Point



- ▶ Compact and elegant (iF design award winner 2006)
- ▶ Single cable for power and communication
- ▶ Mountable on ceiling, wall, or floor stand for best reception
- ▶ Secure, digitally protected, wireless communication
- ▶ Typical range 30 m (100 ft)

The DCN Wireless Access Point (WAP) links the central control unit (WCCU) and the wireless discussion units. To ensure security, data exchange between the WAPs and the wireless discussion units is digitally protected.

The WAP is linked to the WCCU using Bosch's proprietary optical network, which provides digital optical communication and power supply over a single cable. The second optical network connector on the WAP allows the system network to be expanded from a single branch to a redundant loop configuration. In this 'loop-through' configuration, DCN Wireless can be interfaced with compatible Bosch equipment such as Audio Expanders, CobraNet™ interfaces and the Integrus language distribution system.

Secure wireless communication between the WAP and the discussion units is in the 2.4 GHz band, which is license-free worldwide.

The WAP unit's award winning design enables it to be placed unobtrusively on a wall, ceiling, or floor stand by using the universal mounting bracket.

Functions

Controls and Indicators

- LEDs show status of wireless system

Interconnections

- Two optical network connections (second connection can be used in 'loop-through' network)

Installation/Configuration Notes



DCN-WAP mounted on a LBC 1259/00 floor stand

Technical Specifications

Electrical

Power consumption 4 W

Mechanical

Mounting Ceiling, Wall or Floor Stand (using included bracket)

Dimensions (H x W x D) with bracket 59 x 284.5 x 201 mm (2.3 x 11.2 x 7.9 in)

Weight with bracket 907 g (2 lb)
without bracket 643 g (1.4 lb)

Color Light grey (RAL 000 7500)

Ordering Information

DCN-WAP Wireless Access Point DCN-WAP
 light grey color, universal mounting bracket included

Accessories

DCN-WFCCU Flight Case for WCCU and WAP DCN-WFCCU
 light grey, holds wireless central control unit (s), access point & cable

LBC 1259/00 Universal Floorstand LBC 1259/00
 lightweight aluminum construction, foldable, M10 x 12 reducer flange

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: + 31 40 2577 284
 Fax: +31 40 2577 330
 emea.securitysystems@bosch.com
 www.boschsecurity.com

Americas:
 Bosch Security Systems, Inc.
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
 security.sales@us.bosch.com
 www.boschsecurity.us

Asia-Pacific:
 Bosch Security Systems Pte Ltd
 38C Jalan Pemimpin
 Singapore 577180
 Phone: +65 6319 3450
 Fax: +65 6319 3499
 apr.securitysystems@bosch.com
 www.boschsecurity.com

Represented by